

## CRD2000RU10

Cradle for OPN2002

### + Models

**CRD2000U10** Multi-cradle,  
10 slots, USB communication,  
charging

**CRD2000RU10** Multi-cradle,  
10 slots, RS232 + USB  
communication, charging

### + Specifications

#### Communication

- RS232: Baudrate 9600 bps - 115.2 kbps, DB9F connector
- USB: Ver. 1.1, client, VCP, USB-A connector

#### Power

- Voltage requirement: 6V
- Battery charging time: Ca. 2.5 hours

#### Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 30 - 85% (non-condensing)
- Humidity in storage: 20 - 85% (non-condensing)

#### Physical

- Dimensions (w x h x d):  
218 x 81 x 105 mm / 8.58 x 3.19 x 4.13 in
- Weight body: 342 g / 12.1 oz
- Case: ABS, Black

#### Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

#### Enclosed items

- USB cable
- RS232 cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A



Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang
- **Brazil:** São Paulo

Opticon Sensors Europe B.V  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com